



AP - 534EK

Features

- ❖ Heavy duty steel safe body reinforced with steel bar all around front edges to offer you a high level of protection.
 - ❖ Six 25mm diameter locking bolts are made of solid steel
 - ❖ Quality UL certified SecuRam electronic safe lock mounted on hardened steel plate.
 - ❖ Secondary relocking system.
 - ❖ Mechanical override (operates on ROSS six-lever pick resistant safe lock) for digital lock.
 - ❖ Manager's after hours lock (lever lock mounted on hardened steel plate).
 - ❖ All locks are mounted on hardened steel plate.
 - ❖ Programmable administrator code, two manager codes and 28 user codes.
 - ❖ Built in safeguards against tampering - if any incorrect code is keyed in more than three consecutive times, the safe will automatically stay locked.
 - ❖ Programmable time delay up to 99 minutes.
 - ❖ Dual Mode (two codes are required to open safe if needed)
 - ❖ Metal keypad housing.
- Operates on one 9 volt battery.
- ❖ Backlit LCD screen - on screen programming and battery voltage monitor.
 - ❖ Four 15mm holes are provided in back panel for fixing with bolts.
 - ❖ Up to 245 key hooks can be placed to suit single small keys to large vehicle keys.

- ❖ Three removable key panels with each panel having up to 70 key hooks.
- ❖ Carry handle and folding stand on each removable key panel
- ❖ 245 re-usable key tags.
- ❖ 245 printed number labels for key hooks.



Entry Pad



Manager's after hours lock



Specifications

Model	Ext. Dimensions * H x W x D (mm)	Body Thickness	Door Thickness	Weight *	Capacity	RETAIL PRICE (inc GST)
AP - 534EK	530 x 370 x 290	3mm	10mm	48Kg	245 KEYS	

SECUGUARD® safes are covered by a twelve month warranty excluding freight & travelling.

* Weights and dimensions are approximate.

The safe pictures shown on this brochure are for illustrative purpose only.

We reserve the right to alter specifications without notice or obligation